

2kg dry powder fire extinguisher with plastic shutter

code : 002

ERP : 200-001-002



APPLICATIONS

Especially designed for protection in cars, trucks, buildings, offices, production facilities, warehouses, garages.

BASIC FEATURES

- Easy & ergonomic use.
- Fast & effective fire extinguishing.
- Inexpensive maintenance & service.
- The non-return valve on the back side of the manometer, makes the control of the fire extinguisher easier.
- The cylinder is dyed with polyester dye, resistant to the solar radiation.




QUALITY AND SAFETY

It is manufactured according to the local markets' as well as the European standards Κατασκευάζεται σύμφωνα με τις απαιτήσεις της εγχώριας αγοράς και της ΕΕ as it complies to ISO 9001, EN3 & 2014/68/EE.



TECHNICAL CHARACTERISTICS

Extinguishing efficiency	13A 89B C
Extinguishing agent weight	2kg
Propellant gas	N ₂ (nitrogen)
Discharge time	9 s
Testing pressure	27 bar
Operating pressure	10 bar
Temperature range	-30°C +60°C
Total weight	3,5kg
Fire under voltage	1000 V
Height (A)	355mm
Cylinder diameter (B)	110mm



info@flamecontrol.gr

www.flamecontrol.gr

20 Sokratous St. Metamorfofi, 14451, Attica
T: +30 210 6208 500

FLAMECONTROL