

6kg dry powder fire extinguisher suitable for up to 90kV

code : 005-90KV

ERP : 200-001-007



APPLICATIONS

Especially designed for protection in cars, trucks, buildings, offices, production facilities, warehouses, garages, as well as residences. Suitable for highways, railways and marine transportations.

BASIC FEATURES

- Easy & ergonomic use.
- Fast & effective fire extinguishing.
- Inexpensive maintenance & service.
- The non-return valve on the back side of the manometer, makes the control of the fire extinguisher easier.
- The cylinder is dyed with polyester dye, resistant to the solar radiation.



QUALITY AND SAFETY


It is manufactured according to the local markets' as well as the European standards, as it complies to ISO 9001, EN3 & 2014/68/EE. Approved by the PPC for its dielectric strength to 90kV, according to the 131/2017/EΔΔ certificate.

Also suitable instead of the the 12kg dry powder fire extinguisher, according to the 14281 Φ.702.9 clarification of PPC.



TECHNICAL CHARACTERISTICS

Extinguishing efficiency	43A 233B C
Extinguishing agent weight	6kg
Propellant gas	N ₂ (nitrogen)
Discharge time	15 s
Testing pressure	27 bar
Operating pressure	15 bar
Temperature range	-30°C +60°C
Total weight	9,3kg
Fire under voltage	90kV
Height (A)	495mm
Cylinder diameter (B)	160mm



info@flamecontrol.gr

www.flamecontrol.gr

20 Sokratous St. Metamorfosi, 14451, Attica
T: +30 210 6208 500

FLAMECONTROL