


# 6kg dry powder fire extinguisher

ERP : 129-001-007



## ● TECHNICAL CHARACTERISTICS

|                          |                 |
|--------------------------|-----------------|
| Type                     | Stored pressure |
| Extinguishing agent      | ABC dry powder  |
| Capacity (kg)            | 6               |
| Height (mm)              | 530 ±3          |
| Cylinder diameter (mm)   | Φ154            |
| Cylinder volume (lt)     | 6.78            |
| Operating pressure (bar) | 15              |
| Testing pressure (bar)   | 27              |
| Weight (kg)              | 9.4             |
| Discharge time (second)  | 19              |
| Temperature range        | -30°C +60°C     |
| Fire rating              | 43A-233B        |
| Support type             | Wall mounting   |
| EN3 approved             | ✓               |
| Marine approved          | ✓               |

Accepted by PPC for dielectric resistance at 35kV based on test certificate 131/2017 / EDD.

Suitable instead of the 12kg dry powder fire extinguisher, according to No. Prot. 14281 Φ.702.9 clarification of the Fire Service.



info@flamecontrol.gr

www.flamecontrol.gr

**FLAMECONTROL**

20 Sokratous St. Metamorfosi, 14451, Attica

**T: +30 210 6208 500**