



Fire suppression systems FK-5-1-12

For ship engine compartments

The specific system consists of:

- Certified cylinder with extinguishing agent FK-5-1-12.
- Automatic sprinkler activation at 93°C.
- Flexible distribution hose for extinguishing agent with appropriate nozzles.
- Lever for remote manual activation via wire rope.
- Certified for maritime use.



ERP	For spaces up to (m³)	Cylinder Volume (L)	Nominal charge (Kg)	Max tube length (m)	Cylinder diameter (mm)	Max dimensions L x H (mm)	* Weight (Kg)
201-018-001	1,5	1,25	0,80	2	85	120x350	2,55
201-018-002	3,0	1,25	1,60	2	85	120x350	3,35
201-018-003	5,0	2,50	2,70	2	110	130x400	5,10
201-018-004	7,5	4,30	4,00	2	130	145x455	7,20
201-018-005	8,5	4,30	4,50	3	130	145x455	7,70
201-018-006	10,0	4,30	5,30	3	130	145x455	8,50
201-018-007	12,5	7,30	6,60	3	160	180x500	11,15
201-018-008	15,0	7,30	7,90	4	160	180x500	12,45
201-018-009	18,0	7,30	9,50	5	160	180x500	14,05
201-018-012	20,0	10,70	10,50	6	170	190x620	16,20